




BEARING BOWER CORP.



15 mm x 28 mm x 7 mm 7218 B-TVP-UA Bearing 90x160x30mm

Bearing No. 6902

6902 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 15x28x7 mm |
| Bore Diameter | 15 mm |
| Outer Diameter | 28 mm |
| Width | 7 mm |
| d | 15 mm |
| D | 28 mm |
| B | 7 mm |
| C | 7 mm |
| r min. | 0,3 mm |
| da min. | 17 mm |
| da max | 17 mm |
| Da max. | 26 mm |
| ra max. | 0,3 mm |
| Weight | 0,015 Kg |
| Basic dynamic load rating (C) | 4,35 kN |
| Basic static load rating (C0) | 2,26 kN |
| (Grease) Lubrication Speed | 26 000 r/min |
| (Oil) Lubrication Speed | 30 000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.01 |
| EAN | 0029176030000 |
| Product Group | B00308 |



BEARING BOWER CORP.

| | |
|---------------------------------|---|
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nskamericas.com |
| Manufacturer Item Number | 6902 |
| Weight / LBS | 0.016 |
| Outer Race Width | 0.276 Inch 7 Millimeter |
| Bore | 0.591 Inch 15 Millimeter |
| Outside Diameter | 1.102 Inch 28 Millimeter |
| bore diameter: | 15 mm |
| internal clearance: | C0 |
| outside diameter: | 28 mm |
| dynamic load capacity: | 4350 N |
| overall width: | 7 mm |
| precision rating: | ABEC1, P0 |



BEARING BOWER CORP.

| | |
|-----------------------|--------------------------|
| bore type: | Round |
| finish/coating: | Uncoated |
| closure type: | Open |
| cage material: | Steel Cage |
| row type & fill slot: | Single Row Non-Fill Slot |
| maximum rpm: | 30000 rpm |
| snap ring included: | Without Snap Ring |
| SRI | 2.05 |
| hidYobi | 6902 |
| LangID | 1 |
| D_ | 28 |
| SREX | 0.015 |
| B_ | 7 |
| da min | 17 |
| hidTable | ecat_NSRDGB |
| Oil rpm | 30000 |
| SRE | 2.05 |
| mass | 0.015 |
| GRS rpm | 26000 |
| ra | 0.3 |
| SRIX | 0.015 |
| D_a | 26 |
| SRIN | -0.015 |
| C0 | 2.26 |
| fo | 14.3 |
| SREN | -0.015 |
| DE_ | 25.469 |
| Prod_Type3 | DGBB_SR_OT |
| DA_ | 3.969 |
| bomp | 0 |
| Z_ | 10 |
| yobi | 6902 |
| | |



BEARING BOWER CORP.

| | |
|--------|--------|
| C_conv | 4350 |
| ALPHA_ | 0 |
| SDM_ | 21.5 |
| r | 0.3 |
| KBRG | 6101 |
| SBRG | 19 |
| DI_ | 17.531 |